

VETROSPACE L

FITS AS MANY AS 6

Spacious enough to act as a large meeting room or a customer service point, this pod is a comfortable, soundproof space that will keep everyone feeling refreshed and ready to work. You can design and furnish it according to your needs from a variety of options.



[VIEW ONLINE →](#)



Plug-and-play solutions



Automated, smart CO2-controlled ventilation



Best-in-class soundproofing



Easy access for people with mobility limitations



Advanced two-stage air filtration (coarse and HEPA 13)



Antimicrobial LED lighting



Antimicrobial surface nanocoating



ISO 7 indoor air quality performance

TECHNICAL SPECS

Exterior dimensions	W310 / D210 / H240 cm W122 / D82.7 / H94.5 in
Exterior material	LP-laminate
Interior dimensions	W300 / D200 / H220 cm W118.1 / D78.7 / H86.6 in
Interior material	Acoustic ECOfelt lining
Weight	1300 kg 2860 lbs
Indoor surface area	6 m ² 64.5 ft ²
Installation height requirement	>250 cm >98.5 in
Fire safety	UL 723: Class A-C (surface) ASTM E648: Class 1 (flooring)
Electrical safety	IEC 60335-1:2020 UL 962 (E514776)
Seismic safety	Special SEISMIC Certification (2019-0176-COC-01-00), International Building Code (IBC) 2018 (23.02.2021), California Building Code (CBC) 2019 (23.02.2021)
Door	Patented sliding door
Glass thickness	16.7 mm 0.66 in sound-control safety glass
Sound reduction	Ds: 31.3 dB (ISO 23351-1) 43-46dB Rw Lab. STI: 0.03
Ventilation system	Advanced two-stage air filtration (coarse and HEPA 13)
Air flow	Max. 100 l/s
Pressure	Positive air pressure
Lighting	VLD antimicrobial LED
Surface treatment	Photocatalytic antimicrobial nanocoating
Power supply	110-240 VAC / 16 A / 50-60 Hz
Power	100 W average, 550 W maximum
Power sockets	4 as standard

